

PRODUCT TECHNICAL DATASHEET

H93/RX2LP/I



CODE	DESCRIPTION	PCS/PALLET
H93/RX2LP/I	Plug-in receiver, dual code, fixed code / rolling code, 2 channels, 433,92 Mhz, AM / FM. Fixed code: 1000 codes - Rolling code: 250 codes (in basic mode), 1000 codes (in advanced mode). Version exclusively pre-installed on board BRUSHLESS automations equipped with B70/MODLP module (low-power module).	10

PRODUCT TECHNICAL SPECIFICATIONS	
Standard power	5V DC
Absorption	15mA
Operating temperature	-10+55°C
Number of channels	2
Codification	Fix code or Rolling Code
Modulation	AM/ASK - FM/FSK
Carried frequency	433.92 MHz
Exit	Open collector
Storable codes	Fixed code: 1000 - Rolling code: 250 (in basic mode), 1000 (in advanced mode)
Sensibility	-107 dBm
Input impedance	50
Installation Type	Installed on board automations with Brushless control unit and LOW POWER B70/MODLP module
Maximum dimension product in mm (L x W x H)	45 x 35 x 12
Product weight packed (Kg)	0,02
Number items per pallet/box	10

PRODUCT DIMENSIONS AND PREPARING FOR INSTALLATION

